

MSDS - Material Safety Data Sheet**Product Name: Sheen 21 Carpet Shampoo****MSDS No.: 178****I. Basic Information:**

Manufacturer: Clausen Mfg.
Address: Box 473
City, ST Zip: Mansfield, OH 44901

Last Update: 1/ 6/00

Chemical State: Liquid Gas Solid

Chemical Type: Pure Mixture



1	Health
0	Flammability
0	Reactivity
B	Pers. Protection

II. Ingredients:

CAS No.	Chemical Name	% Range	EHS	NTP	IARC	SARA SUB Z 313	OSHA PEL	ACGIH TLV	Other Limits
111762	Butoxy ethanol	1-10%							
151213	Sodium lauryl sulfate	1-10%							

III. Hazardous Identification:**Hazard Category:**

Acute Chronic Fire Pressure Reactive

Hazardous Identification Information:

Causes mild irritation on contact.

IV. First Aid Measures:**Route(s) of Entry:**

Eye, skin, ingestion, inhalation

Health Hazards (Acute and Chronic):

Prolonged breathing of vapor or prolonged skin contact may result in damage to the liver, kidneys, lungs and blood-forming organs.

Signs and Symptoms:

Eyes-Redness, mild irritation. Skin-Redness, skin irritation, nausea, dizziness may result from breathing vapors or from absorption thorough skin. Swallowing-Ingesting large quantities may cause vomiting and diarrhea. Prolonged or repeated breathing of vapors or prolonged skin contact may result in damage to the liver, kidneys, lungs, and blod-forming organs.

Medical Conditions Generally Aggravated by Exposure:

Non known.

Emergency and First Aid Procedures:

Eyes-Flush immediately with water for at least 15 minutes. If irritation occurs seek medical attention. Skin-Wash with soap and water. Ingestion-Induce vomiting. Keep head below hips to prevent aspiration of liquids into lungs. Inhalation-Remove exposed person to fresh air. Treat symptomatically. Call a physician.

Other Health Warnings:

MSDS - Material Safety Data Sheet

Product Name: Sheen 21 Carpet Shampoo

MSDS No.: 178

V. Fire Fighting Measures:

Flash Point: >100F **Lower Explosive Limit:** NA **Upper Explosive Limit:** NA
Fire Extinguishing Media: CO2, dry chemical, foam, water spray

Special Fire Fighting Procedures:

Use water to cool fire-exposed surfaces and to protect personnel. Combustable liquid.

Unusual Fire and Explosion:

None Known

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Eliminate sources of ignition. Flush area with plenty of water. Large spills should be collected for disposal.

VII. Handling and Storage:

Precautions to be Taken:

Do not get in eyes, on skin or clothing. Keep away from heat and open flame. Use with adequate ventilation. Wash thoroughly after handling.

Other Precautions:

NA.

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

Not needed under normal conditions of use.

Personal Protective Equipment:

Protective gloves-Rubber Eye protection-Safety goggles or glasses
Other protective clothing may be needed if splashing occurs.

IX. Physical and Chemical Properties:

Boiling Point: 212F **Melting Point:** NA **Evaporation Rate:** NA
Vapor Pressure (mm Hg.): NA **Vapor Density (AIR = 1):** NA
Solubility In Water: Complete
Appearance and Odor: Clear, liquid, fruity odor.
Other Information: NA

X. Stability and Reactivity:

Stability:

Stable.

Incompatibility (Materials to Avoid):

Strong oxidizers.

MSDS - Material Safety Data Sheet

Product Name: Sheen 21 Carpet Shampoo

MSDS No.: 178

Decomposition/By Products:

Non known.

Hazardous Polymerization:

Will not occur.

XI. Toxicological Information:

Not established.

XII. Ecological Information:

Not established.

XIII. Disposal Considerations:

Dispose of in accordance with applicable federal, state and local ordinances.

XIV. Transport Information:

NA.

XV. Regulatory Information:

NA.

XVI. Other Information:

EMERGENCY TELEPHONE NO. 419-524-5112

Distributed by-G & L Supply 139 N. Diamond St. Mansfield, Oh 44901
The Janton Company 1288 N. High St. Columbus, Oh 43201

No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to information concerning the product referred to in this material safety data sheet.